

## Schottky Barrier Diode

VOLTAGE RANGE: 60V


PEAK PULSE POWER: 200mW

### FEATURES

- Low Forward Voltage Drop
- Guard Ring Construction for Transient
- Protection Negligible Reverse Recovery Time
- Very Low Reverse Capacitance

### MECHANICAL DATA

- Case: SOD-323 Small Outline Plastic Package
- Polarity: Color band denotes cathode end
- Mounting Position: Any



### MAXIMUM RATINGS AND CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified

Symbol	Parameter	Value	Unit
<b>V<sub>RRM</sub></b>	Repetitive Peak Reverse Voltage	60	V
<b>V<sub>RWM</sub></b>	Working Peak Reverse Voltage		
<b>V<sub>R</sub></b>	DC Blocking Voltage		
<b>V<sub>R(RMS)</sub></b>	RMS reverse voltage	42	V
<b>I<sub>FM</sub></b>	Forward Continuous Current	15	mA
<b>I<sub>FSM</sub></b>	Non-repetitive Peak Forward Surge Current @t=8.3ms	2	A
<b>P<sub>D</sub></b>	Power Dissipation	200	mW
<b>R<sub>OJA</sub></b>	Thermal Resistance from Junction to Ambient	500	°C/W
<b>T<sub>j</sub></b>	Junction Temperature	125	°C
<b>T<sub>stg</sub></b>	Storage Temperature	-50~+150	°C

### Electrical Specification (T<sub>A</sub>=25@25°C unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
<b>Reverse voltage</b>	V(BR)	I <sub>R</sub> =10μA	60			V
<b>Reverse current</b>	I <sub>R</sub>	V <sub>R</sub> =50V			0.2	μA
<b>Forward voltage</b>	VF	I <sub>F</sub> =1mA			0.41	V
		I <sub>F</sub> =15mA			1	
<b>Total capacitance</b>	C <sub>tot</sub>	V <sub>R</sub> =0V,f=1MHz			2	pF
<b>Reverse recovery time</b>	t <sub>rr</sub>	I <sub>F</sub> =I <sub>R</sub> =5mA, I <sub>rr</sub> =0.1×I <sub>R</sub> , R <sub>L</sub> =100Ω			1	ns

MARKING: S1



HFZT

# RATINGS AND CHARACTERISTIC CURVES

## Typical Characteristics

